



## Revitalize Communication with 4,000-lm-class WUXGA<sup>1</sup> Portable Laser Projectors

### ■ Main Features

#### 01 | Effortless Projection Anywhere

LMZ460 Series weighs just 4.2 kg (9.26 lbs) and has a compact body that's easy to carry and install. Project content from standby in about one second<sup>4</sup>, link control with the source via CEC command-compatible<sup>5</sup> HDMI®, and install flexibly with new Digital Zoom Extender and Image Shift function.



#### 02 | Efficient, Reliable, and Cost-Effective

SOLID SHINE Laser and reusable ECO Filter don't need replacement for 20,000 hours<sup>6</sup>, slashing maintenance cost, time, effort, and wastage compared to a lamp projector. High-efficiency optical engine reduces energy consumption by 20 %<sup>7</sup> compared to conventional lamp-based models, saving resources.



#### 03 | SOLID SHINE for Clear Images in Bright Light

Inspire your students or colleagues with clear, sharp pictures even in brightly lit rooms with up to 4,600 lm<sup>8</sup> brightness and 3,000,000:1<sup>9</sup> Dynamic Contrast. WUXGA<sup>1</sup> panels reproduce images at their original aspect ratio and offer extra image height when projecting webpages and spreadsheets.

#### PT-LMZ460 Series

	PT-LMZ460	PT-LMZ420	PT-LMW460	PT-LMW420	PT-LMX460	PT-LMX420
Light Output	4,600 lm <sup>8</sup>	4,200 lm <sup>8</sup>	4,600 lm <sup>8</sup>	4,200 lm <sup>8</sup>	4,600 lm <sup>8</sup>	4,200 lm <sup>8</sup>
Resolution	WUXGA		WXGA		XGA	

<sup>1</sup> PT-LMZ460/LMZ420: WUXGA (1920 x 1200), PT-LMW460/LMW420: WXGA (1280 x 800), PT-LMX460/LMX420: XGA (1024 x 768). <sup>2</sup> Supports signals up to 4K/30p. A signal with different resolution is converted to the number of display dots. PT-LMZ460/LMZ420: 1920 x 1200 dots, PT-LMW460/LMW420: 1280 x 800 dots, PT-LMX460/LMX420: 1024 x 768 dots. <sup>3</sup> Optional AI-WM50 Series Wireless Module required (sold separately). Product availability may vary by country or region. <sup>4</sup> When [ECO MANAGEMENT] > [QUICK STARTUP] is set to [ON], [QUICK STARTUP] is unavailable after the [AVAILABLE PERIOD] setting has expired. When [QUICK STARTUP] is set to [ON], the projector continues to warm up, increasing power consumption. When [QUICK STARTUP] is set to [ON], the standby period when the [QUICK STARTUP] function is valid will be added as the projector runtime. [QUICK STARTUP] cannot be set when [STANDBY MODE] is set to [ECO]. May vary depending on connection terminals, signals, and other conditions. <sup>5</sup> Depending on the connected CEC command-compatible device, the link control may not operate normally. <sup>6</sup> Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C [86 °F], elevation 700 m [2,297 ft] with 0.15 mg/m<sup>3</sup> of particulate matter). Estimated time until light output declines to 50 % varies depending on environment. Filter cleaning cycle varies depending on the environment. Filter can be washed and reused up to two times (see Operating Manual for details). Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m<sup>3</sup>), 10,000 hours (under dust conditions of 0.15 mg/m<sup>3</sup>). <sup>7</sup> PT-LMZ460/LMZ420 (240 V maximum power consumption, AC 100–240 V) compared to PT-LB426 Series (300 W maximum power consumption, AC 100–240 V) in NORMAL Mode. <sup>8</sup> When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL]. Measurement, measuring conditions, and method of notation are all compliant with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. <sup>9</sup> Full On/Full Off, when [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1]. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.

## Clear Pictures Wherever You Go

LMZ460 Series is highly portable and easy to install. It delivers up to 4,600 lm<sup>1</sup> for vibrant pictures in brightly lit rooms. Text is crisp and smooth thanks to 3,000,000:1<sup>2</sup> Dynamic Contrast and WUXGA<sup>3</sup> resolution. Start instantly with projection from standby in about one second<sup>4</sup>, and reduce distractions with quiet 23 dB<sup>5</sup> operation.

## Smooth and Easy UX

Two CEC-command-compatible<sup>6</sup> HDMI® inputs allow LMZ460 Series to start up and project content automatically, just press play on your device. Wireless projection<sup>7</sup> is simplified with QR code connection, or try Wireless Presentation System PressIT<sup>®</sup> to share your screen with a single button-press. 5 V/2 A USB port and 4K input-signal<sup>9</sup> compatibility streamline integration.

<sup>1</sup> Refer to specifications for brightness values of individual models. When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL]. Measurement, measuring conditions, and method of notation are all compliant with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. <sup>2</sup> Full On/Full Off, when [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1]. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. <sup>3</sup> PT-LMZ460/LMZ420: WUXGA (1920 x 1200), PT-LMW460/LMW420: WXGA (1280 x 800), PT-LMX460/LMX420: XGA (1024 x 768). <sup>4</sup> When [ECO MANAGEMENT] > [QUICK STARTUP] is set to [ON], [QUICK STARTUP] is unavailable after the [AVAILABLE PERIOD] setting has expired. When [QUICK STARTUP] is set to [ON], the projector continues to warm up, increasing power consumption. When [QUICK STARTUP] is set to [ON], the standby period when the [QUICK STARTUP] function is valid will be added as the projector runtime. [QUICK STARTUP] cannot be set when [STANDBY MODE] is set to [ECO]. May vary depending on connection terminals, signals, and other conditions. <sup>5</sup> For PT-LMZ420/LMW420/LMX420 in QUIET Mode (33 dB in NORMAL/ECO Mode), PT-LMZ460/LMW460/LMX460: 24 dB (QUIET Mode), 35 dB (NORMAL/ECO Mode). <sup>6</sup> Depending on the connected CEC command-compatible device, the link control may not operate normally. <sup>7</sup> Optional AI-WM50 Series Wireless Module (sold separately) is required to enable wireless functions including connection via QR code. Product availability may vary by country or region. Free software is available for Windows® PC at <https://panasonic.net/cns/projector/download/application/>. Panasonic Wireless Projector app available at the App Store or the Google Play store. Please check device and OS compatibility before download and installation. <sup>8</sup> Sold separately. Product availability may vary by country or region. For more information, visit <https://panasonic.net/cns/prodisplays/pressit/>. <sup>9</sup> Supports signals up to 4K/30p. A signal with different resolution is converted to the number of display dots. PT-LMZ460/LMZ420: 1920 x 1200 dots, PT-LMW460/LMW420: 1280 x 800 dots, PT-LMX460/LMX420: 1024 x 768 dots. <sup>10</sup> Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of particulate matter). Estimated time until light output declines to 50 % varies depending on environment. Filter cleaning cycle varies depending on the environment. Filter can be washed and reused up to two times (see Operating Manual for details). Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m<sup>3</sup>), 10,000 hours (under dust conditions of 0.15 mg/m<sup>3</sup>). <sup>11</sup> PT-LMZ460/LMZ420 (240 W maximum power consumption, AC 100–240 V) compared to PT-LB426 Series (300 W maximum power consumption, AC 100–240 V) in NORMAL Mode. <sup>12</sup> PT-LMZ460/LMZ420 only. <sup>13</sup> Resolution decreases when using Digital Zoom Extender and Image Shift. Some screen correction functions are not available when using this function, and range of corner adjustment is limited. Use of the same projector mount position may not be possible in every situation. <sup>14</sup> When Digital Zoom Extender is set to 80 %.

## Specifications

Model	PT-LMZ460	PT-LMZ420	PT-LMW460	PT-LMW420	PT-LMX460	PT-LMX420
Projector type	LCD projectors					
LCD panel	Size				16.0 mm (0.63 in) diagonal (4:3 aspect ratio)	
	Pixels				786,432 (1024 x 768) pixels	
Light source	Laser diodes					
Light output <sup>1,2</sup>	4,600 lm	4,200 lm	4,600 lm	4,200 lm	4,600 lm	4,200 lm
Time until light output declines to 50 % <sup>3</sup>	20,000 hours (NORMAL/QUIET)/24,000 hours (ECO)					
Resolution	WUXGA (1920 x 1200 pixels)		WXGA (1280 x 800 pixels)		XGA (1024 x 768 pixels)	
Contrast ratio <sup>1</sup>	3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)					
Screen size (diagonal)	0.76–7.62 m (30–300 in), 16:10 aspect ratio				0.76–7.62 m (30–300 in), 4:3 aspect ratio	
Center-to-corner zone ratio <sup>1</sup>	85 %					
Lens	1.2x manual zoom (throw ratio: 1.36–1.64:1), manual focus lens, F 1.61–1.76, f 19.1–23.0 mm				1.2x manual zoom (throw ratio: 1.47–1.77:1), manual focus lens, F 1.61–1.76, f 19.1–23.0 mm	
Digital Zoom Extender <sup>4</sup>	Throw ratio: 1.36–2.05:1 <sup>5</sup> (Corresponding value. When used together with optical zoom.)				Throw ratio: 1.47–2.22:1 <sup>5</sup> (Corresponding value. When used together with optical zoom.)	
Keystone correction range	Vertical: ±25 ° (Auto, Manual), Horizontal: ±35 ° (Manual)		Vertical: ±35 ° (Auto, Manual), Horizontal: ±35 ° (Manual)			
Terminals	HDMI 1/2 IN	HDMI 19-pin x 2 (Compatible with HDCP 1.4, Deep Color, 4K/30p <sup>6</sup> signal input), CEC supported <sup>7</sup>				
	COMPUTER 1 IN	D-sub 15-pin (female) x 1 (RGB/YPbPr/YCbCr)				
	COMPUTER 2 IN	D-sub 15-pin (female) x 1 (RGB/YPbPr/YCbCr)				
	AUDIO 1/2 IN	M3 stereo mini-jack x 2				
	AUDIO OUT	M3 stereo mini-jack x 1				
	SERIAL IN	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)				
	LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX				
USB (VIEWER/WIRELESS/DC OUT)	USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A <sup>9</sup> )					
Protocol versions	IPv4					
Power supply	AC 100 V–240 V, 50/60 Hz					
Power consumption <sup>9</sup>	Maximum power consumption	240 W		230 W		
	On-mode power consumption (Light Power)	[NORMAL]: 215 W (100–240 V), 205 W (200–240 V) [ECO]: 165 W (100–240 V), 160 W (200–240 V) [QUIET]: 160 W (100–240 V), 155 W (200–240 V)		[NORMAL]: 205 W (100–240 V), 195 W (200–240 V) [ECO]: 155 W (100–240 V), 145 W (200–240 V) [QUIET]: 150 W (100–240 V), 145 W (200–240 V)		
Built-in speaker	10 W monaural					
Filter <sup>10</sup>	Included (Estimated maintenance time: approx. 20,000 hours)					
Operation noise <sup>1</sup>	35 dB (NORMAL/ECO), 24 dB (QUIET)	33 dB (NORMAL/ECO), 23 dB (QUIET)	35 dB (NORMAL/ECO), 24 dB (QUIET)	33 dB (NORMAL/ECO), 23 dB (QUIET)	35 dB (NORMAL/ECO), 24 dB (QUIET)	33 dB (NORMAL/ECO), 23 dB (QUIET)
Dimensions (W x H x D)	349 mm x 105 mm x 309 mm (13 3/4" x 4 1/8" x 12 5/32") (with feet at shortest position)					
Weight with supplied lens <sup>11</sup>	Approx. 4.2 kg (9.26 lbs)					
Operating environment	Operating temperature: 0–45 °C (32–113 °F) <sup>12</sup> , Operating humidity: 20–80 % (no condensation)					
Applicable software	Multi Monitoring & Control Software, Projector Network Setup Software, Logo Transfer Software, Presenter Light Software for Windows <sup>®13</sup> , Wireless Projector App for iOS/Android <sup>™14</sup>					
Control function via LAN	PJLink <sup>®</sup> [Class 2], Crestron Connected <sup>®</sup> , AMX Device Discovery					

<sup>1</sup> Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. <sup>2</sup> When [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF], and [AUTO POWER SAVE] is set to [OFF]. <sup>3</sup> Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of particulate matter). Estimated time until light output declines to 50 % varies depending on environment. <sup>4</sup> Resolution decreases when using this function. V/H Keystone Correction and curved-screen correction are not available when using this function, and range of corner adjustment is limited. <sup>5</sup> When Digital Zoom Extender is set to 80 %. <sup>6</sup> 4K signals are converted to the projector's resolution upon projection. <sup>7</sup> Depending on the connected CEC command-compatible device, the link control may not operate normally. <sup>8</sup> On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready. <sup>9</sup> Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). <sup>10</sup> Filter cleaning cycle varies depending on environment. Filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m<sup>3</sup>), 10,000 hours (under dust conditions of 0.15 mg/m<sup>3</sup>). <sup>11</sup> Average value. May differ depending on the actual unit. <sup>12</sup> Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level. When optional AI-WM50 Series Wireless Module is attached, operating temperature range becomes 0–40 °C (32–104 °F). <sup>13</sup> When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy, while images and sound are being transmitted. <sup>14</sup> When using the Wireless Projector app, display resolution differs depending on your iOS/Android<sup>®</sup> device and the display device. The maximum supported display resolution is WXGA (1280 x 800).

## Optional Accessories

- **Ceiling Mount Bracket**  
ET-PKL100H (for high ceilings) / ET-PKL100S (for low ceilings)  
Note: ET-PKL100H/PKL100S used in combination with ET-PKL420B (sold separately).
- **Projector Mount Bracket** ET-PKL420B
- **Replacement Filter Unit** ET-RFL400

## Efficient, Reliable, and Economical

Make the change to eco-friendly Panasonic projection. Laser light-source and reusable ECO Filter don't need replacement until 20,000 hours<sup>10</sup>, reducing waste, cost, and hassle. LMZ460 Series is also more efficient, using 20 %<sup>11</sup> less energy than conventional lamp-based models with maximum power consumption of just 240 W.

## Simple to Adjust and Install

Screen adjustment includes Automatic Vertical Keystone Correction, 4-Corner and Horizontal/Vertical Keystone Correction, 6-Point Correction<sup>12</sup>, and Curved Screen Correction. Digital Zoom Extender<sup>13</sup> allows you to keep the same mount position as your old projector if it's beyond optical zoom range, while Digital Image Shift moves the image 10%<sup>14</sup> in any direction, great for off-axis projection.

## Other Features

- Built-in 10 W speaker, mic input, audio output, and shutter function
- DICOM Simulation Mode
- Supports PJLink<sup>™</sup>, Crestron Connected<sup>™</sup>, and AMX<sup>®</sup> DD
- Control emulation function
- Custom startup logo and anti-theft features
- Free 360° installation
- ECO Management System
- Presentation Support System

# Panasonic CONNECT

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Availability of products and accessories may vary by country or region. Products may be subject to export control regulations. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. Trademark PJLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. Windows<sup>®</sup> is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. SOLID SHINE and PressIT are trademarks of Panasonic Holdings Corporation. All other trademarks are the property of the respective trademark owners. © Panasonic Connect Co., Ltd. 2022.



For more information about Panasonic projectors, please visit:  
Projector Global Website – <https://panasonic.net/cns/projector/>  
Facebook – [www.facebook.com/panasonicprojectoranddisplay](https://www.facebook.com/panasonicprojectoranddisplay)  
YouTube – [www.youtube.com/user/PanasonicProjector](https://www.youtube.com/user/PanasonicProjector)

Note: Following the shift of the Panasonic Group to a holding company system, the Connected Solutions Company of the Panasonic Corporation has changed to Panasonic Connect Co., Ltd. as of April 1, 2022.

All information included here is valid as of September 2022.

LMZ460series\_G1 Printed in Japan.