



S-S40E-K (Black)



## Designed for everyday shooting



## S40

Lumix S Fixed Focal Lens  
40mm/ F2

S-S40E-K  
EAN 5025232989881 | RRP: 399€  
Customs tariff number : 85258900000  
Country of origin : China (CN)  
Packaging : 11,4 x 11,4 x 13,3 cm / 0,31 kg

A compact, lightweight prime designed for everyday versatility, the LUMIX S 40mm F2 delivers natural-looking images with beautiful bokeh — ideal for street photography, portraits, and landscapes.

Featuring a 40mm focal length, this single focal length lens delivers a natural perspective suited to a wide range of scenes. Its bright F2 maximum aperture creates soft and beautiful bokeh for strong subject separation in portraits and helps maintain faster shutter speeds in low-light to keep clear images without pushing ISO unnecessarily.

With an overall length of approx. 4.1cm and a weight of approx. 144g, it pairs perfectly with the compact body of the LUMIX S9, creating a lightweight, portable setup that's easy to carry. And while remaining compact and lightweight, the lens features a dust- and splash-resistant design for reliability in changing weather conditions.

To meet the growing demand for video production, the lens also incorporates features such as focus breathing suppression and micro-step aperture control, enabling smooth exposure transitions and high-quality video expression.

### 1. Natural 40mm View with large F2 Aperture

- 40mm focal length provides a natural perspective similar to human field of view
- Large F2 aperture produces soft and beautiful bokeh

### 2. Compact, Easy-to-Carry Design

- Compact & lightweight design: approx. 40.9mm in length and approx. 144g in weight
- Shares the same compact size and 62mm filter thread as the LUMIX S 18-40mm F4.5-6.3

### 3. Enhanced control and reliability

- Features a control ring and focus button for intuitive and easy operation
- Dust- and splash-resistant design for reliable shooting in various conditions

MOUNT	L-Mount
FOCAL LENGTH	40 mm
MAXIMUM APERTURE	F2.0
MINIMAL APERTURE	F22
DIAGONAL ANGLE OF VIEW	57°
APERTURE TYPE	7 diaphragm blades
CLOSEST FOCUSING DISTANCE	30 cm
MAXIMUM MAGNIFICATION	0,17x
LENS CONSTRUCTION	7 elements in 6 groups (3 asph. lenses); Fluorine Coating
IMAGE STABILISATION	--
DUST, SPLASH AND FREEZE RESISTANT	yes / yes / yes (-10°C to 40°C)
OTHER FEATURES	Customizable Focus Ring, Focus Button (Fn Button), AF/MF Switch
FILTER SIZE	62 mm
SIZE	approx. 69,4 x 40,9 mm
WEIGHT	approx. 144 g
PACKAGING	11,4 x 11,4 x 13,3 cm/ 0,31 kg
STANDARD ACCESSORIES	Lens front cap, lens rear cap